

Status:	Ok
Approval:	05.08.2021

Classification	Public series
Product type:	Coated abrasives
Main industries:	General Fabrication
Further industries:	Trucks Rail Marine Bus Wind Power Casting and Forging Machinery, equipment





Product profile	
Grit type:	Zirconia alumina
Grit range (total):	40; 60-80; 120 ANSI FEPA P / ISO 6344
Backing:	X-wt cloth
Coating:	Closed
Bonding:	Resin over resin
Special coating:	Cooling additive
Equipment:	


Properties	Technology
Removal rate:	8 - high
Lifetime:	8 - long
Finishing:	7 - good
Flexibility:	3 - rigid
Contact pressure:	8 - strong

Advantages	
General Fabrication:	<ul style="list-style-type: none"> - High performance due to zirconia alumina abrasive grit - Consistent surface quality until the abrasive is completely worn - Cost reduction thanks to long lifetime

Applications	
General Fabrication:	<ul style="list-style-type: none"> - Weld preparation - Removal of discolouration - Stock removal - Surface treatment - Deburring

Material	
General Fabrication:	Steel ● Unalloyed / low-alloy steel

Conversion forms	Upper conversion	Lower conversion
	Rolls	- Cloth rolls - Jumbolino
	Discs	- siafix discs
	Flap discs	- Fibreglass pads - Plastic pads
	Belts	- spiralbands

Application	Superordinate group	Subgroup
	Portable machine sanding	Angle grinder
Cut:	Dry application	

Details	
No suitability for:	<ul style="list-style-type: none"> - Wood sanding - Wet sanding - Stone grinding
Sanding recommendation:	
Safety recommendation:	<p>Observe the current valid safety recommendations at: www.sia-abrasives.com > Expertise > Safety</p> <ul style="list-style-type: none"> - Pay attention to the abrasives safety data sheet (available from sia Abrasives) - Follow the general FEPA safety recommendations - Use eye and face protection - Use an effective dust extraction unit or wear a fine dust mask

Communication	
Claim:	For market-leading performance in steel applications
Copy:	Designed for general treatment of unalloyed or low-alloy steel, 2824 siaflap with zirconia alumina and its robust cloth backing provides a high removal rate and long lifetime. Another advantage is the consistent surface quality until the abrasive has been completely used up.
Image material:	Product Top View (PTV)
	Front side: ID
	Rear side: ID
	Application image
	General Fabrication: ID 8068
	Product show:
	Macro shot:
	Packaging image:
	Product group image: ID 8118

- Main application
- Secondary application