



1948 siaflex

Flexible and versatile



Flexible and versatile

As an all-round series for wet and dry sanding, 1948 siaflex produces outstanding results in all available grits and in a variety of automotive applications.

- ▶ High performance for stock removal with good finish
- ▶ Highly flexible and adaptable to contours
- ▶ Minimal clogging thanks to open coating in 220 - 600 grit range
- ▶ Long lifetime
- ▶ Suitable for general use in dry and wet sanding applications
- ▶ Versatile all-round product with an attractive range of options

Product profile

Grit type:	Blue-fired / white aluminium oxide	
Grit range:	40; 60-1500	
Backing:	Latex paper (FSC-certified)	
Coating:	Electrostatic	P040 – P180
	Electrostatic open	P220 – P600
	Electrostatic	800
Bonding:	Resin over resin	
Special coating:	Stearate	P180 – 800

Use



Applications

- Sanding of coatings and impurities
- Sanding out unevenness at the edges of repaired surfaces
- Flatting of bodyfiller and primer filler
- Fine sanding of primer filler
- Keying of old and new lacquers
- Removal of orange peel effect and dust inclusions

Materials

Colour; Primer filler; Bodyfiller; Lacquer; Old lacquer; Primer coat; Epoxy primer coat; Cathodic dip primer coat; Plastics; Acrylic glass; Gelcoat polyester; Glass-fibre reinforced plastic (GRP); Composite; Aluminium; steel

Technology

Open coating; Plain; S Performance; siafast; siasoft