




7979 siasponge flat

For dry and wet sanding in hard-to-reach areas

Medium	120–180
Fine	240–320
Superfine	500–600
Ultrafine	800–1000
Microfine	1200–1500



For dry and wet sanding in hard-to-reach areas

Applications such as keying, fine sanding and scuffing are especially easy to do using 7979 siasponge soft. Its high flexibility ensures that it adapts perfectly to contours, curves and profiles to deliver a high-quality, consistent sanding pattern.

- ▶ Can be used wet or dry
- ▶ Colour coded for easy identification
- ▶ Low clogging thanks to 3D properties imparted by foam, binder system and grit
- ▶ For hard-to-reach areas and round profiles
- ▶ Regular scratch depth due to consistent grinding performance
- ▶ Minimal risk of sanding through from high contact pressure

Product profile

Grit type:	Aluminium oxide
Grit range:	60; 100-220; 280-320
Backing:	Foam (open structure)
Coating:	Mechanical
Bonding:	Elastic binder
Coating:	1-sided

Applications

- Keying of wood and plastics
- Keying of conventional old and new varnishes, primer filler and paints
- Fine sanding of primer filler in hard-to-reach areas
- Producing a matt finish on varnishes
- Flatting of primer filler
- Intermediate sanding of varnishes

Use



Materials

Colour; Primer filler; Primer coat; Plastics; Old lacquer; Composite