



1944 siaone

the one with cut



the one with cut

The quality with aggressive cut and optimum lifetime. For price-conscious users for working with various materials, for example: bodyfiller, primer filler, varnish, paint and wood.

- ▶ Aggressive initial sanding thanks to optimised sanding grain
- ▶ Process stability thanks to uniform scratch depths in all grits
- ▶ Excellent price/performance ratio

Product profile

Grit type:	Aluminium oxide	P040 – P500
Grit range:	40; 60-240; 320; 400-500	
Backing:	c-wt paper (FSC-certified)	P040 – P100
	b-wt paper (FSC-certified)	P120 – P500
Coating:	Electrostatic	
Bonding:	Resin over resin	
Special coating:	Stearate	P220 – P500

Use



Applications

- Sanding off rusted parts
- Sanding off old varnish, paints and stains
- Sanding off old paint and varnish
- Sanding off raised wooden fibres
- Sanding floorboards
- Sanding wooden terraces and pool surrounds
- Sanding off brittle or poorly adhesive paints
- Keying or sanding surfaces
- Keying smoothed surfaces
- Keying surfaces for better paint adhesion
- Fine sanding of surfaces
- Flattening uneven areas
- Flattening lightweight construction walls

Materials

Soft wood; Hard wood; Resinous wood; Water-based lacquer; Solid surface material; Old paint; Old lacquer; Primer filler; Primer coat; Bodyfiller; Plastics; Mineral fibreboard; Plaster; Dry wall lining boards

Technology

siafast